

JetNet 3810G

Industrial 8 PoE + 2 GbE Booster PoE Switch

Vehicle with 12~24V



CE FC RoHS

- 2 Giga Uplink
- 12~24VDC Booster
- 65W*
- QoS
- 25~60°C

- 8 10/100 TX PoE plus two 10/100/1000TX uplink ports
- Vehicle PoE: DC 12V~24V input, deliver 8 port PoE @48V
- 802.3af compliant PoE: Total power budget is 65W* with max. 15.4W per port
- Two gigabit Ethernet ports for larger uplink bandwidth of surveillance
- Support QoS for optimizing video and VoIP stream
- Fault relay for active warning of port failure
- -25~60°C operating temperature

Overview

JetNet 3810G is an Industrial PoE Boost Switch designed with 8 Fast Ethernet PoE ports and 2 Gigabit uplink ports to ensure high-bandwidth uplink connection for large-scale surveillance in transportation system networks. JetNet 3810G integrates Korenix patented vehicle PoE technology – the 12~24V to 48V power booster for making the deployment of standard PoE IP cameras feasible on buses, railcars, ships, etc. Moreover, the compact size with aluminum alloy metal enclosure allows JetNet 3810G to reliably operate under -25~60°C wide temperature range applications.

12~24V Power Booster to 48V PoE

JetNet 3810G, designed with Korenix patented DC 12~24V to 48V boost technology, is the best solution for the vehicle PoE applications, where DC 48V power supply is not available. With the built-in power booster, the JetNet 3810G can be powered by DC

12~24V to deliver 15.4W per port and 65W* per unit at DC 48V and 60°C to PoE-enabled devices such as IP cameras, PoE Wireless APs, PoE IP phones...etc. and therefore, be easily applied in vehicles or carriages.

Gigabit Bandwidth and QoS supported

JetNet 3810G features eight PoE ports and two uplink gigabit Ethernet ports. Customers can connect up to 8 IP cameras and provide guaranteed large image uplink bandwidth connection. In addition, the JetNet 3810G supports QoS to ensure the high quality of video traffic transmission by simply adjusting the priority of data transfer.


Fault Relay function provided

JetNet 3810G provides fault relay to automatically warn users if any abnormal situation occurs. As a result, users can quickly handle the emergency and shorten the failover time.

*Specifications may change without prior notice

- Industrial Intelligent NMS
- Rackmount PoE Plus Switch
- Industrial PoE Plus Switch
- Industrial 12-24V PoE Switch**
- Industrial PoE Switch
- Rackmount L3/L2 Switch
- Gigabit Managed Switch
- Managed Ethernet Switch
- Entry-level Switch
- IP67/68 Ethernet Switch
- Wireless Outdoor AP
- Embedded PoE/Router Computer (LINUX)
- Industrial Communication Computer (WIN/LINUX)
- Ethernet/PoE/Serial Board
- Ethernet I/O Server
- Media Converter
- Serial Device Server
- SFP Module
- Din Rail Power Supply

Dimensions



Hardware Specifications

Technology

Standard:

IEEE 802.3 10Base-T Ethernet
 IEEE 802.3u 100Base-TX Fast Ethernet
 IEEE 802.3ab 1000Base-T
 IEEE802.3x Flow Control and Back-pressure
 IEEE 802.3af Power Over Ethernet
 IEEE 802.1p Class of Service

Performance

Switch Technology: Store and Forward Technology with 32Gbps Switch Fabric

System Throughput: 14,880pps for 10M Ethernet, 148,800pps for 100M Fast Ethernet, 1,488,100pps for Gigabit Ethernet

Transfer packet size: 64 bytes to 1522 bytes for untagged and tagged frames

MAC Address: 8k

Packet Buffer: 1 Mbits

Interface

Configuration: 802.3af compliant PoE ports x 8
 10/100/1000Base-TX x 2
 Auto MDI/MDI-X, Auto Negotiation

Cables:

10 Base-T: 2-pair UTP/STP Cat. 3,4,5 cable (100m)
 100 Base-Tx: 2-pair UTP/STP Cat. 5 cable (100m)
 1000 Base-T: 4-pair UTP/STP Cat. 5 cable (100m)
 10Base-T: 4-pair UTP/STP Cat 3,4,5, 100ohm (100m) for PoE
 100Base-Tx: 4-pair UTP/STP Cat.5, 100ohm (100m) for PoE

LED per unit:

PoE (Green) x8
 Fault alarm (Red) x1
 Power on/ off (Green on/ off) x1

LED on Ethernet port:

Link/ Activity (Green on/ blinking)
 Gigabit copper: Link/Act (Green on/ Blinking)
 Full duplex/ Collision (Yellow on/ Blinking)
 Gigabit copper: Speed (Yellow Blinking)

Relay Alarm: Dry Relay output with 1A@24V ability

POE technology: Alternative B

Power Requirements

Power: 12~24V

Power Consumption: 30W without PoE, 95W with PoE

Mechanical

Construction:

Rugged Aluminum Alloy Chassis

Mounting: DIN-Rail mount

Dimension:

66(W) x 149(H) x 131.2(D) mm (with Din-rail clip)

Net weight: 1.05kg

Environment

Operating Temp: -13 ~ 140°F(-25 ~ 60°C), 5 to 95% RH

Storage Temp: -40 ~ 176°C(-40 ~ 80°C), 5 to 95% RH

EMI: FCC class A, CE/EN55022 Class A

EMC: EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11

Shock: IEC60068-2-27 (50g peak acceleration)

Vibration: IEC60068-2-6 (5g/5~500Hz/random operation)

MTBF: at least 200,000 hours @ 25°C

Warranty: 5 years

*Pending

Ordering Information

JetNet 3810G Industrial 8 PoE+2GbE Booster PoE Switch

Includes:

- JetNet 3810G
- Attached 4-pin power terminal block
- Quick installation guide
- Documentation and software CD-ROM

Industrial Intelligent NMS

Rackmount PoE Plus Switch

Industrial PoE Plus Switch

Industrial 12-24V PoE Switch

Industrial PoE Switch

Rackmount L3/L2 Switch

Gigabit Managed Switch

Managed Ethernet Switch

Entry-level Switch

IP67/68 Ethernet Switch

Wireless Outdoor AP

Embedded PoE/Router Computer (LINUX)

Industrial Communication Computer (WIN/LINUX)

Ethernet/PoE/ Serial Board

Ethernet I/O Server

Media Converter

Serial Device Server

SFP Module

Din Rail Power Supply